

976 nm laser diode

10 W- 105 μ m fiber – NA=0.22*

Reference: 976LD-3-0-0

Technology : Single emitter with VBG**

	Unit	Min	Typ	Maximum
Output Power (nominal/Kink free)	W	9/10		
Center Wavelength	nm	975.5	976	976.5
Spectral Width (FWHM)	nm		<0.7	
Threshold Current	A		0.9	
Operating Current	A			13
Operation Voltage	V		1.6	1.8
Wavelength shift w Temperature	nm/°C		0.02	
Wavelength shift w current	nm/A			
Feedback isolation	nm	1020		1200
	dB	30		
Slope Efficiency	W/A		0.9	
Storage case Temperature	°C	-40 (abs. min)		70 (abs max)
Operating case temperature	°C	20 (abs min)		30 (abs max)
Fiber Bend Radius	mm	50 (abs min)		
Fiber Buffer/tube Diameter	μ m		245/900	
Fiber Clad Diameter	μ m		125	
Fiber Core Diameter	μ m		105	
Numerical Aperture	NA			0.22*
Soldering Temperature	°C			260
Soldering time	s			10
Integrated thermistor	No			
Fiber connector	Yes – SMA905***			

Please solder the pins when the level of current is over 6A

*: Light NA within the fiber is typically much lower

**: Volume Bragg Grating

***: Fiber connector for handling and space or collimator-coupling- not for SMA-SMA fiber-to-fiber connection

Form factor:

